

Abrasive mop disc

SMT 926 SPECIAL



Properties

Grain	Zirconia alumina
Backing plate	Glass fibre
Design	Convex 6°
Aggression	■■■■■■■□
Service life	■■■■■■■■

Product benefit

Maximum removal rate and service life - Especially suitable for rough work on steel and stainless steel - Optimal removal rate when used on high power angle grinders under increased grinding pressure

Materials

Stainless steel	●
Steel	●

Applications

- ▶ Locksmith's shop
- ▶ Oil and gas industry
- ▶ Steel construction

Available grits:


16	20	24	30	36	40	50	60	80	100	120	150	180	220	240	280	320	360	400	500	600	800	1000	1200	1500	2000	3000
----	----	----	----	----	----	----	----	----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	------	------	------	------	------

Diameter x Bore in mm	Form	grain	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
115 x 22,23		40	80 m/s	13300 rpm	10	321703
115 x 22,23		60	80 m/s	13300 rpm	10	321706
115 x 22,23		80	80 m/s	13300 rpm	10	321708
125 x 22,23		40	80 m/s	12250 rpm	10	321704
125 x 22,23		60	80 m/s	12250 rpm	10	321707
125 x 22,23		80	80 m/s	12250 rpm	10	321709

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany
 Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
 sales@klingspor.de - www.klingspor.de



Diameter x Bore in mm	Form	grain	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
180 x 22,23		40	80 m/s	8500 rpm	10	321705

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de

