Pleated mop

FSR 618



Properties

Bonding agent	Resin
Grain	Aluminium oxide

Materials

Metals	●
Wood	◑
Paint/Varnish/Filler	◑
Plastic	◑

Product benefit

Pleated mop wheel consisting of pleated aluminum oxide cloth flaps allows easy access to joints, grooves and slots - Very large immersion depth

Available grits:

16 20 24 30 36 40 50 60 80 100 120 150 180 220 240 280 320 360 400 500 600 800 1000 1200 1500 2000 2500 3000

Diameter x Bore in mm	grain	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
165 x 14	40	50 m/s	5800 rpm	10	10187
165 x 14	60	50 m/s	5800 rpm	10	5830
165 x 14	80	50 m/s	5800 rpm	10	5831
165 x 14	120	50 m/s	5800 rpm	10	73994
165 x 14	150	50 m/s	5800 rpm	10	25998
165 x 14	220	50 m/s	5800 rpm	10	26033

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de