

Data Sheet

SW 501 TR Abrasive block, abrasive sponge for Paint, Varnish, Filler, Wood

New
extremely tear-resistant



Applications

| | |
|---------|---|
| Paint | ● |
| Varnish | ● |
| Filler | ● |
| Wood | ● |
| Plastic | ⊕ |
| Metals | ⊕ |

Properties

| | |
|---------|-----------------|
| Grain | Aluminium oxide |
| Coating | Close |

Advantages: Satin surface scratch pattern - For low and high profiled surfaces (two usable sides) - Crease and break-resistant - Washable and reusable - Extremely tear-resistant - Solvent free bonding with grit size dependent colouring

| Width /mm | Length /mm | Height /mm | Density | Grit | type of grain | Cat.number | Availability |
|-----------|------------|------------|---------|------|---------------|------------|--------------|
| 96 | 123 | 12,5 | soft | 100 | Alumina | 351573 | |
| 96 | 123 | 12,5 | soft | 150 | Alumina | 353263 | |
| 96 | 123 | 12,5 | soft | 120 | Alumina | 353264 | |
| 96 | 123 | 12,5 | soft | 180 | Alumina | 351574 | |
| 96 | 123 | 12,5 | soft | 220 | Alumina | 353262 | |