

Backing pad, plain/flexible

ST 358



Product benefit

Medium-hard backing pad allows good adaptation to the workpiece
- For universal use, especially for surface and finish grinding (grit 50 and finer) - High temperature resistance

Diameter in mm	holding device	Suitable for	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
100	thread M10	Diameter 100 x 16	80 m/s	15300 rpm	1	305190
100	thread M14	Diameter 100 x 22	80 m/s	15300 rpm	1	2774
115 X-LOCK	X-LOCK	Ø 115 X-LOCK	80 m/s	13300 rpm	1	352049
115	thread M10	Diameter 115 x 22	80 m/s	13300 rpm	1	14859
115	thread M14	Diameter 115 x 22	80 m/s	13300 rpm	1	14838
125 X-LOCK	X-LOCK	Ø 125 X-LOCK	80 m/s	12200 rpm	1	352048
125	thread M14	Diameter 125 x 22	80 m/s	12200 rpm	1	14835
150	thread M14	Diameter 150 x 22	80 m/s	12000 rpm	1	14836
180	thread M14	Diameter 180 x 22	80 m/s	8500 rpm	1	14840
235	thread M14	Diameter 235 x 22	80 m/s	6600 rpm	1	14841

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany

Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186

sales@klingspor.de - www.klingspor.de

