


Abrasive cloth, waterproof

CS 416 Y



Properties

Bonding agent	Resin
Grain	Zirconia alumina
Coating	Semi-open
Backing	Y-polyester

Product benefit

Very high aggressiveness and abrasive performance - Long service life also when used on materials that cause clogging

Materials

Stainless steel	●
Plastic	●
NF metals	●

Applications

- ▶ Railing construction
- ▶ Wall and façade builder
- ▶ Apparatus and container manufacturing
- ▶ Foundries

Available grits:

16	24	30	36	40	50	60	80	100	120	150	180	220	240	280	320	360	400	500	600	800	1000	1200	1500	2000	2500	3000
----	----	----	----	----	----	----	----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	------	------	------	------	------	------

Width x Length in mm	grain	type of joint	type of coat.abras.	Packing unit/pcs.	Cat. number
75 x 2000	36	F4G butt joint	CS 416 Y	10	204858
75 x 2000	40	F4G butt joint	CS 416 Y	10	205377
75 x 2000	60	F4G butt joint	CS 416 Y	10	207651
75 x 2000	80	F4G butt joint	CS 416 Y	10	220805
150 x 2000	36	F4G butt joint	CS 416 Y	10	231336
150 x 2000	40	F4G butt joint	CS 416 Y	10	205474

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany
 Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
 sales@klingspor.de - www.klingspor.de



Width x Length in mm	grain	type of joint	type of coat.abras.	Packing unit/pcs.	Cat. number
150 x 2000	60	F4G butt joint	CS 416 Y	10	204213
150 x 2000	80	F4G butt joint	CS 416 Y	10	205130

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany

Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186

sales@klingspor.de - www.klingspor.de

