Abrasive fibre disc, multibond

CS 570



Properties

Bonding agent	Resin
Grain	Zirconia alumina
Coating	Close

Materials

Stainless steel	●
Aluminium	●
NF metals	◑

Product benefit

Self-sharpening effect - High aggressiveness, especially suitable for stainless steel - Increase in performance due to low temperatures - Multibond prevents heat tinting - Especially suitable for use on aluminium

Applications

- Stainless steel processing industry

Available grits:

16 20 24 30 **36** **40** **50** **60** **80** **100** **120** 150 180 220 240 280 320 360 400 500 600 800 1000 1200 1500 2000 2500 3000

Diameter x Hole in mm	Hole pattern	grain	Vmax m/s	Max. RPM	type of coat.abras.	bore shape	Packing unit/pcs.	Cat. number
100 x 16	⊙ 10	36	80 m/s	15300 rpm	CS 570	round hole	25	204823
100 x 16	⊙ 10	60	80 m/s	15300 rpm	CS 570	round hole	25	204825
100 x 16	⊙ 10	80	80 m/s	15300 rpm	CS 570	round hole	25	204826
100 x 16	⊙ 10	120	80 m/s	15300 rpm	CS 570	round hole	25	204828
115 x 22	⊛ 30	36	80 m/s	13300 rpm	CS 570	star shaped hole	25	204086
115 x 22	⊛ 30	50	80 m/s	13300 rpm	CS 570	star shaped hole	25	204087

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de

Diameter x Hole in mm	Hole pattern	grain	Vmax m/s	Max. RPM	type of coat.abras.	bore shape	Packing unit/pcs.	Cat. number
115 x 22	⊛ 30	60	80 m/s	13300 rpm	CS 570	star shaped hole	25	204088
115 x 22	⊛ 30	80	80 m/s	13300 rpm	CS 570	star shaped hole	25	204089
115 x 22	⊛ 30	100	80 m/s	13300 rpm	CS 570	star shaped hole	25	204090
115 x 22	⊛ 30	120	80 m/s	13300 rpm	CS 570	star shaped hole	25	204091
115 x 22	⊙ 10	36	80 m/s	13300 rpm	CS 570	round hole	25	204797
115 x 22	⊙ 10	60	80 m/s	13300 rpm	CS 570	round hole	25	204799
115 x 22	⊙ 10	80	80 m/s	13300 rpm	CS 570	round hole	25	204800
115 x 22	⊙ 10	120	80 m/s	13300 rpm	CS 570	round hole	25	204802
115 x 22	⊛ 30	40	80 m/s	13300 rpm	CS 570	star shaped hole	25	250258
125 x 22	⊛ 30	36	80 m/s	12250 rpm	CS 570	star shaped hole	25	204093
125 x 22	⊛ 30	50	80 m/s	12250 rpm	CS 570	star shaped hole	25	204094
125 x 22	⊛ 30	60	80 m/s	12250 rpm	CS 570	star shaped hole	25	204095
125 x 22	⊛ 30	80	80 m/s	12250 rpm	CS 570	star shaped hole	25	204096
125 x 22	⊛ 30	100	80 m/s	12250 rpm	CS 570	star shaped hole	25	204097
125 x 22	⊛ 30	120	80 m/s	12250 rpm	CS 570	star shaped hole	25	204098
125 x 22	⊙ 10	36	80 m/s	12250 rpm	CS 570	round hole	25	204806
125 x 22	⊙ 10	60	80 m/s	12250 rpm	CS 570	round hole	25	204811
125 x 22	⊙ 10	80	80 m/s	12250 rpm	CS 570	round hole	25	204812
125 x 22	⊙ 10	120	80 m/s	12250 rpm	CS 570	round hole	25	204814
125 x 22	⊛ 30	40	80 m/s	12250 rpm	CS 570	star shaped hole	25	250259
180 x 22	⊛ 30	36	80 m/s	8500 rpm	CS 570	star shaped hole	25	204100
180 x 22	⊛ 30	60	80 m/s	8500 rpm	CS 570	star shaped hole	25	204102
180 x 22	⊛ 30	80	80 m/s	8500 rpm	CS 570	star shaped hole	25	204103
180 x 22	⊛ 30	120	80 m/s	8500 rpm	CS 570	star shaped hole	25	204105

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de