Cutting-off wheel

A 24 N SUPRA

Properties

Bonding agent	Synthetic resin, fibre-reinforced
Type of grain	Aluminium oxide
Bond	■■■□□□□
Aggression	■■■■■□□
Service life	■■■■■□□

Materials

Stainless steel	●
Aluminium	◑

Applications

- Stainless steel processing industry
- Railing construction

Product benefit

Special recipe prevents smearing and clogging - High removal rate on stainless steel due to hardened aluminium oxide

Diameter x Width x Bore in mm	Form	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
115 x 2,5 x 22,23		80 m/s	13300 rpm	25	3020
125 x 2,5 x 22,23		80 m/s	12250 rpm	25	2951
150 x 2,5 x 22,23		80 m/s	10200 rpm	25	235377
180 x 3 x 22,23		80 m/s	8500 rpm	25	13455
230 x 3 x 22,23		80 m/s	6650 rpm	25	13463
230 x 3 x 22,23		80 m/s	6650 rpm	25	13477

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de