

# Cutting-off wheel

# A 36 R SUPRA



## Properties

Bonding agent	Synthetic resin, fibre-reinforced
Type of grain	Aluminium oxide
Bond	■■■■□□□
Aggression	■■■■■■■□
Service life	■■■■■■■□

## Product benefit

Excellent cutting performance - Optimized aggression and service life

## Materials

Stainless steel ●

## Applications

- ▶ Plant engineering
- ▶ Apparatus and container manufacturing
- ▶ Metal construction
- ▶ Locksmith's shop
- ▶ Stainless steel processing industry
- ▶ Railing construction

Diameter x Width x Bore in mm	Form	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
115 x 2 x 22,23		80 m/s	13300 rpm	25	123208
125 x 2 x 22,23		80 m/s	12200 rpm	25	126849
150 x 2 x 22,23		80 m/s	10200 rpm	25	251752
180 x 2,5 x 22,23		80 m/s	8500 rpm	25	123209
230 x 2,5 x 22,23		80 m/s	6600 rpm	25	123833

**Klingspor Schleifsysteme GmbH und Co. KG**

Hüttenstraße 36 - 35708 Haiger - Germany

Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186

sales@klingspor.de - www.klingspor.de

