

Cutting-off wheel

A 60 TZ SPECIAL



Properties

Bonding agent	Synthetic resin, fibre-reinforced
Type of grain	Aluminium oxide
Bond	■■■■■■■□
Aggression	■■■■■■■□
Service life	■■■■■■■□

Product benefit

Free of iron, sulfur and chlorine - Short cutting times - Minimal burr formation - Low thermal load

Materials

Stainless steel	●
Steel	●
NF metals	⦿

Applications

- ▶ Plant engineering
- ▶ Apparatus and container manufacturing
- ▶ Metal construction
- ▶ Locksmith's shop
- ▶ Stainless steel processing industry
- ▶ Railing construction

Diameter x Width x Bore in mm	Form	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
100 x 1 x 16		80 m/s	15300 rpm	25	202402
115 x 1 x 22,23		80 m/s	13300 rpm	25	202400
115 x 1 x 22,23		80 m/s	13300 rpm	25	233741
125 x 1 x 22,23		80 m/s	12250 rpm	25	202401
125 x 1 x 22,23		80 m/s	12250 rpm	25	233742
125 x 1 x 22,23 X-LOCK		80 m/s	12250 rpm	25	351258

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany
 Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
 sales@klingspor.de - www.klingspor.de

