


Cutting-off wheel

A 624 SX SUPRA



Properties

Bonding agent	Synthetic resin, fibre-reinforced
Type of grain	Aluminium oxide
Bond	■■■■□□□
Aggression	■■■■■■■■■
Service life	■■■■■■□□

Product benefit

For universal use on all rail types - Top performing product for lower powered machines (<5kW) and hard rails - Fast cutting, due to softer bond - For use on gas powered cutting-off machines with a cutting speed of 100 m/s and clamping device

Materials

Steel ●

Applications

► Railway construction

Diameter x Width x Bore in mm	Form	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
305 x 3,5 x 22,23	— —	100 m/s	6400 rpm	10	353111
356 x 4 x 22,23	— —	100 m/s	5500 rpm	10	351433
356 x 4 x 25,4	— —	100 m/s	5500 rpm	10	340641
406 x 4 x 25,4	— —	100 m/s	4800 rpm	10	351436

Klingspor Schleifsysteme GmbH und Co. KG
 Hüttenstraße 36 - 35708 Haiger - Germany
 Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
 sales@klingspor.de - www.klingspor.de

