

# Cutting-off wheel

# A 946 TZ SPECIAL



## Properties

Bonding agent	Synthetic resin, fibre-reinforced
Type of grain	Aluminium oxide
Bond	■■■■■■■■■
Aggression	■■■■■■■■■
Service life	■■■■■■■□

## Product benefit

Free of iron, sulfur and chlorine - Extra long service life across all applications - For universal use in metal processing - Short cutting times - Low burr formation - Low thermal load - 25 pieces delivered in the Kronenflex® box for long lasting high performance and moisture protection

## Materials

Steel	●
Stainless steel	●
NF metals	○
Castings	○

## Applications



- ▶ Plant engineering
- ▶ Apparatus and container manufacturing
- ▶ Metal construction
- ▶ Locksmith's shop
- ▶ Stainless steel processing industry
- ▶ Railing construction

Diameter x Width x Bore in mm	Form	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
115 x 1,6 x 22,23	— —	80 m/s	13300 rpm	25	339109
125 x 1,6 x 22,23	— —	80 m/s	12200 rpm	25	339110
150 x 1,6 x 22,23	— —	80 m/s	10200 rpm	25	339111
180 x 1,6 x 22,23	— —	80 m/s	8500 rpm	25	339112

### Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany  
 Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186  
 sales@klingspor.de - www.klingspor.de



Diameter x Width x Bore in mm	Form	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
230 x 1,9 x 22,23		80 m/s	6600 rpm	25	339113
230 x 1,9 x 22,23		80 m/s	6600 rpm	25	339114

**Klingspor Schleifsysteme GmbH und Co. KG**

Hüttenstraße 36 - 35708 Haiger - Germany

Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186

sales@klingspor.de - www.klingspor.de

