# Cutting-off wheel

# C 24 EXTRA

## Properties

| | |
|---|---|
| Bonding agent | Synthetic resin, fibre-reinforced |
| Type of grain | SiC |
| Bond | ■■■■□□□ |
| Aggression | ■■■■□□□ |
| Service life | ■■■■□□□ |

## Materials

| | |
|---|---|
| Stone/Concrete | ● |
| Titanium | ● |

## Applications

- Gardening and landscaping
- Stonemason businesses

## Product benefit

Universal cutting-off wheel for all mineral materials - Wide application range due to sharp, coarse SiC grit

| Diameter x Width x Bore in mm | Form | Vmax m/s | Max. RPM | Packing unit/pcs. | Cat. number |
|---|---|---|---|---|---|
| 115 x 2,5 x 22,23 |  | 80 m/s | 13300 rpm | 25 | 242143 |
| 115 x 2,5 x 22,23 |  | 80 m/s | 13300 rpm | 25 | 188462 |
| 125 x 2,5 x 22,23 |  | 80 m/s | 12250 rpm | 25 | 242144 |
| 125 x 2,5 x 22,23 |  | 80 m/s | 12250 rpm | 25 | 188464 |
| 180 x 3 x 22,23 |  | 80 m/s | 8500 rpm | 25 | 13489 |
| 230 x 3 x 22,23 |  | 80 m/s | 6650 rpm | 25 | 13491 |
| 230 x 3 x 22,23 |  | 80 m/s | 6650 rpm | 25 | 189003 |

**Klingspor Schleifsysteme GmbH und Co. KG**
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de