

Cutting-off wheel

Z 960 TX SPECIAL



Properties

Bonding agent	Synthetic resin, fibre-reinforced
Type of grain	Zirconia alumina
Bond	■■■■■■■■
Aggression	■■■■■■■■
Service life	■■■■■■■■

Product benefit

Free of iron, sulphur and chlorine - Ideal for tough/hard materials such as high alloy steels - Short cutting times and long service life due to self-sharpening zirconia alumina - Low thermal load - Low burr formation - 25 pieces delivered in the Kronenflex® box for long lasting high performance and moisture protection

Materials

Stainless steel	●
Alloys	●
Carbon steel	●

Applications

- ▶ Stainless steel processing industry
- ▶ Railing construction

Diameter x Width x Bore in mm	Form	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
115 x 1 x 22,23	— —	80 m/s	13300 rpm	25	322184
125 x 1 x 22,23	— —	80 m/s	12250 rpm	25	322185

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany

Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186

sales@klingspor.de - www.klingspor.de

