

Grinding disc

A 624 SUPRA



Fe-S-Cl
<0,1%



Properties

Bond	■ ■ ■ ■ ■ □ □ □
Aggression	■ ■ ■ ■ ■ □ □ □
Service life	■ ■ ■ ■ ■ □ □ □

Product benefit

Two-layer structure for optimum performance balance - Bottom grinding layer: high aggressiveness for fast, consistent stock removal - Top layer: increased wear resistance for extended service life - Suitable for demanding grinding applications in metalworking and maintenance - Free of iron, sulphur and chlorine

Materials

Steel	●
Stainless steel	○
Cast iron	○

Applications

- ▶ Locksmith's shop
- ▶ Metal construction
- ▶ Boat and shipbuilding

Diameter x Width x Bore in mm	Form	Vmax m/s	Max. RPM	Packing unit/pcs.	Cat. number
115 x 6 x 22,23		80 m/s	13300 rpm	10	701967
125 x 6 x 22,23		80 m/s	12250 rpm	10	701968
180 x 6 x 22,23		80 m/s	8500 rpm	10	701971
230 x 6 x 22,23		80 m/s	6650 rpm	10	701940

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany

Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186

sales@klingspor.de - www.klingspor.de

